

# Safety Data Sheet

## MasterProtect EL 750 SM Pas TB

Revision date : 2019/04/30  
Version: 6.0

Page: 1/11  
(30606097/SDS\_GEN\_US/EN)

### 1. Identification

#### Product identifier used on the label

## MasterProtect EL 750 SM Pas TB

#### Recommended use of the chemical and restriction on use

Recommended use\*: Product for construction chemicals  
Recommended use\*: for industrial and professional users

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

Company:  
BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

#### Emergency telephone number

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

#### Other means of identification

Chemical family: Coating

---

### 2. Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

#### Classification of the product

Skin Sens.	1	Skin sensitization
STOT RE	2	Specific target organ toxicity — repeated exposure
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic
Carc.	1A	Carcinogenicity

# Safety Data Sheet

## MasterProtect EL 750 SM Pas TB

Revision date : 2019/04/30  
Version: 6.0

Page: 2/11  
(30606097/SDS\_GEN\_US/EN)

### Label elements

Pictogram:



Signal Word:  
Danger

Hazard Statement:

H317	May cause an allergic skin reaction.
H350	May cause cancer.
H373	May cause damage to organs (Kidney) through prolonged or repeated exposure.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P201	Obtain special instructions before use.
P260	Do not breathe dust/gas/mist/vapours.
P202	Do not handle until all safety precautions have been read and understood.
P273	Avoid release to the environment.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P314	Get medical advice/attention if you feel unwell.
P303 + P352	IF ON SKIN (or hair): Wash with plenty of soap and water.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

### Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Labeling of special preparations (GHS):

Product contains the following components and may cause an allergic skin reaction: 2-octyl-4-isothiazol-3-ones

The substance may cause sensitization of the skin in particularly sensitive individuals. Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

---

### 3. Composition / Information on Ingredients

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

# Safety Data Sheet

## MasterProtect EL 750 SM Pas TB

Revision date : 2019/04/30  
Version: 6.0

Page: 3/11  
(30606097/SDS\_GEN\_US/EN)

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
1317-65-3	>= 15.0 - < 50.0%	Limestone
13463-67-7	>= 5.0 - < 10.0%	Titanium dioxide
107-21-1	>= 1.0 - < 3.0%	ethylene glycol
1314-13-2	>= 0.3 - < 1.0%	Zinc oxide
9036-19-5	>= 0.1 - < 0.2%	Poly(oxy-1,2-ethanediyl), .alpha.-(1,1,3,3-tetramethylbutyl)phenyl]- .omega.-hydroxy-
14808-60-7	>= 0.3 - < 1.0%	crystalline silica
26530-20-1	>= 0.0 - < 0.1%	2-octyl-4-isothiazol-3-ones

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

##### If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

##### If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

##### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

##### If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting.

#### Most important symptoms and effects, both acute and delayed

Hazards: No applicable information available.

#### Indication of any immediate medical attention and special treatment needed

##### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

### 5. Fire-Fighting Measures

#### Extinguishing media

Suitable extinguishing media:  
foam, water spray, dry powder, carbon dioxide

# Safety Data Sheet

## MasterProtect EL 750 SM Pas TB

Revision date : 2019/04/30

Version: 6.0

Page: 4/11

(30606097/SDS\_GEN\_US/EN)

Unsuitable extinguishing media for safety reasons:  
water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

harmful vapours, nitrogen oxides, fumes/smoke, carbon black, carbon oxides

See MSDS section 10 - Stability and reactivity.

### Advice for fire-fighters

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

### Further information:

The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists. Wear eye/face protection. If exposed to high vapour concentration, leave area immediately. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

### Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.

For large amounts: Pump off product.

---

## 7. Handling and Storage

### Precautions for safe handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Protection against fire and explosion:

Product is not explosive.

### Conditions for safe storage, including any incompatibilities

Observe VCI storage rules.

Suitable materials for containers: tinned carbon steel (Tinplate)

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

Protect from temperatures below: 5 °C

The packed product must be protected from temperatures below the indicated one.

Protect from temperatures below: 40 °F

The packed product must be protected from temperatures below the indicated one.

# Safety Data Sheet

## MasterProtect EL 750 SM Pas TB

Revision date : 2019/04/30  
Version: 6.0

Page: 5/11  
(30606097/SDS\_GEN\_US/EN)

### 8. Exposure Controls/Personal Protection

#### Components with occupational exposure limits

ethylene glycol	ACGIH TLV	TWA value 25 ppm Vapor fraction ; STEL value 50 ppm Vapor fraction ; STEL value 10 mg/m3 Aerosol, inhalable. ;
Zinc oxide	OSHA PEL	PEL 15 mg/m3 Total dust ; PEL 5 mg/m3 Respirable fraction ; PEL 5 mg/m3 fumes/smoke ; TWA value 5 mg/m3 fumes/smoke ; TWA value 5 mg/m3 Respirable fraction ; TWA value 10 mg/m3 Total dust ; STEL value 10 mg/m3 fumes/smoke ;
	ACGIH TLV	TWA value 2 mg/m3 Respirable fraction ; STEL value 10 mg/m3 Respirable fraction ;
Limestone	OSHA PEL	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ; TWA value 15 mg/m3 Total dust ;
Titanium dioxide	OSHA PEL	PEL 15 mg/m3 Total dust ; TWA value 10 mg/m3 Total dust ;
	ACGIH TLV	TWA value 10 mg/m3 ;
crystalline silica	OSHA PEL	TWA value 0.05 mg/m3 (Respirable dust); OSHA Action level 0.025 mg/m3 (Respirable dust);
	ACGIH TLV	TWA value 0.025 mg/m3 Respirable fraction ;

#### **Advice on system design:**

No applicable information available.

#### **Personal protective equipment**

##### **Respiratory protection:**

Wear a NIOSH-certified (or equivalent) respirator as necessary.

##### **Hand protection:**

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

##### **Eye protection:**

Safety glasses with side-shields.

##### **Body protection:**

Impermeable protective clothing

##### **General safety and hygiene measures:**

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift.

# Safety Data Sheet

## MasterProtect EL 750 SM Pas TB

Revision date : 2019/04/30

Page: 6/11

Version: 6.0

(30606097/SDS\_GEN\_US/EN)

At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

### 9. Physical and Chemical Properties

Form:	liquid
Odour:	product specific
Odour threshold:	No applicable information available.
Colour:	milky white
pH value:	neutral to slightly alkaline
Melting point:	No applicable information available.
<i>Information on: Water</i>	
Melting point:	0 °C
-----	
Boiling point:	No applicable information available.
<i>Information on: Water</i>	
Boiling point:	100 °C
-----	
Sublimation point:	No applicable information available.
Flash point:	A flash point determination is unnecessary due to the high water content.
Flammability:	not flammable
Lower explosion limit:	No applicable information available.
Upper explosion limit:	No applicable information available.
Autoignition:	Study does not need to be conducted.
Vapour pressure:	No applicable information available.
<i>Information on: Water</i>	
Vapour pressure:	23.4 hPa ( 20 °C) Literature data.
-----	
Density:	approx. 1.00 g/cm <sup>3</sup> ( 20 °C)
Relative density:	No applicable information available.
Vapour density:	No applicable information available.
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	approx. 2.5 mm <sup>2</sup> /s ( 20 °C)
Solubility in water:	( 20 °C) soluble
Miscibility with water:	( 20 °C) miscible
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

### 10. Stability and Reactivity

#### Reactivity

# Safety Data Sheet

## MasterProtect EL 750 SM Pas TB

Revision date : 2019/04/30

Version: 6.0

Page: 7/11

(30606097/SDS\_GEN\_US/EN)

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

### Conditions to avoid

See MSDS section 7 - Handling and storage.

### Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

### Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

---

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact. Virtually nontoxic by inhalation. The product has not been tested. The statement has been derived from the properties of the individual components.

#### Assessment other acute effects

No applicable information available.

#### Irritation / corrosion

Assessment of irritating effects: Based on available Data, the classification criteria are not met.

#### Sensitization

Assessment of sensitization: The product contains 2-n-octyl-4-isothiazolin-3-one (CAS-No.: 26530-20-1). The substance may cause sensitization of the skin in particularly sensitive individuals. Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

### Chronic Toxicity/Effects

# Safety Data Sheet

## MasterProtect EL 750 SM Pas TB

Revision date : 2019/04/30

Version: 6.0

Page: 8/11

(30606097/SDS\_GEN\_US/EN)

### Repeated dose toxicity

Assessment of repeated dose toxicity: The substance may cause damage to the kidney after repeated ingestion of high doses, as shown in animal studies. The substance may cause damage to the kidney after repeated skin contact with high doses.

This product contains crystalline silica (quartz). Prolonged or repeated inhalation of respirable crystalline silica may result in silicosis.

### Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from the properties of the individual components.

### Carcinogenicity

Assessment of carcinogenicity: May cause cancer.

#### *Information on: Titanium dioxide*

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.*

#### *Information on: crystalline silica*

*Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. In long-term animal studies in which the substance was given by inhalation in high doses, a carcinogenic effect was observed. The substance and its compounds in the form of respirable dusts/aerosols classified by the German MAK commission as a category 1 carcinogen (substances that cause cancer to humans). A carcinogenic effect cannot safely be ruled out. The inhalation uptake of the alveolar fraction of the fine dust may cause damage to the lungs. The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.*

*NTP listed carcinogen*

*OSHA (Occupational Safety and Health Administration) has classified this substance as carcinogenic.*

### Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from the properties of the individual components.

### Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from the properties of the individual components.

#### *Information on: ethylene glycol*

*Assessment of teratogenicity: Developmental toxicity was observed after oral ingestion of high doses in studies with rats and mice, but this effect was not seen in a study with rabbits. Mechanistic studies show that the rabbit is the relevant species for the classification for human health. As such, and since ethylene glycol is not a developmental toxicant in the rabbit, no classification is warranted. However, the relevance of this result for humans is unclear.*

### Other Information



# Safety Data Sheet

## MasterProtect EL 750 SM Pas TB

Revision date : 2019/04/30

Version: 6.0

Page: 9/11

(30606097/SDS\_GEN\_US/EN)

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from products of a similar structure and composition.

### Symptoms of Exposure

---

## 12. Ecological Information

### Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms. May cause long-term adverse effects in the aquatic environment. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

### Persistence and degradability

Assessment biodegradation and elimination (H<sub>2</sub>O)

Inherently biodegradable. The insoluble fraction can be removed by mechanical means in suitable waste water treatment plants.

### Bioaccumulative potential

Assessment bioaccumulation potential

No data available.

Discharge into the environment must be avoided.

### Mobility in soil

Assessment transport between environmental compartments

No data available.

### Additional information

Other ecotoxicological advice:

Acutely harmful for aquatic organisms. Do not discharge product into the environment without control. The product has not been tested. The statement has been derived from the properties of the individual components.

---

## 13. Disposal considerations

### Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

### Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

# Safety Data Sheet

## MasterProtect EL 750 SM Pas TB

Revision date : 2019/04/30  
Version: 6.0

Page: 10/11  
(30606097/SDS\_GEN\_US/EN)

### 14. Transport Information

**Land transport**  
USDOT

Not classified as a dangerous good under transport regulations

**Sea transport**  
IMDG

Not classified as a dangerous good under transport regulations

**Air transport**  
IATA/ICAO

Not classified as a dangerous good under transport regulations

### 15. Regulatory Information

#### Federal Regulations

**Registration status:**

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Refer to SDS section 2 for GHS hazard classes applicable for this product.

**EPCRA 313:**

<u>CAS Number</u>	<u>Chemical name</u>
107-21-1	ethylene glycol

#### State regulations

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
PA	13463-67-7	Titanium dioxide
	14808-60-7	crystalline silica
	107-21-1	ethylene glycol
	1317-65-3	Limestone
MA	14808-60-7	crystalline silica
	107-21-1	ethylene glycol
	1317-65-3	Limestone
	13463-67-7	Titanium dioxide
NJ	13463-67-7	Titanium dioxide
	107-21-1	ethylene glycol
	1317-65-3	Limestone
	14808-60-7	crystalline silica

#### **Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:**

**WARNING:** This product can expose you to chemicals including LEAD, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**NFPA Hazard codes:**

Health: 2      Fire: 0      Reactivity: 0      Special:

# Safety Data Sheet

## MasterProtect EL 750 SM Pas TB

Revision date : 2019/04/30  
Version: 6.0

Page: 11/11  
(30606097/SDS\_GEN\_US/EN)

---

### 16. Other Information

**SDS Prepared by:**  
BASF NA Product Regulations  
SDS Prepared on: 2019/04/30

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET